

2100 LED LIGHTBAR™

2147A1H



Powerful LED emergency lighting in a low profile lightbar—just 2.1" tall

Design Features

- Clear Polycarbonate Lens
- Extruded Aluminum Frame
- Four Corner Amber LED Optix Modules Standard
- Amber Optix Modules Standard on Front and Rear. LED X and LC-LED Options Available.
- LED Modules Available in Flashing or Steady Burn
- Red LED Modules Available for Special Market Needs
- Built-in ArrowStik Option with Halogen, Optix, LED X or LC-LED
- LIT3 Mounting Kit Included

Specifications

- Lengths: 36" (914.4 mm), 47" (1193.8 mm), 58" (1473.2 mm), 69" (1752.6 mm)
- 2.1" H x 12.25" W (53.34 mm x 311.15 mm)
- 12 Volt DC
- 0.5 Average Amp Draw per LED Module
- SAE J845 (Steady Burn) / J595 (Strobing), Class I

Standard Models

2136A1H

36" L, (4) Corner Optix LED Modules, (4) Amber Optix LED Modules, (2) MR-11 35w Rear Work Lights, 23 lbs.

2147A1H

47" L, (4) Corner Optix LED Modules, (4) Amber Optix LED Modules, (2) MR-11 35w Rear Work Lights, 27 lbs.

2147A2H

47" L, (4) Corner Optix LED Modules, (4) Amber Optix LED Modules, 6-Lamp Halogen ArrowStik with Deluxe Control Head, 29 lbs.

2147A3H

47" L, (4) Corner Optix LED Modules, (4) Amber Optix LED Modules, 6-Head LED X ArrowStik with Deluxe Control Head, 29 lbs

2147A30H

47" L, (4) Corner Optix LED Modules, (2) Amber Optix LED Modules, 5-Head Optix ArrowStik with Deluxe Control Head, 29 lbs

2147A4H

47" L, (4) Corner Optix LED Modules, (4) Amber Optix LED Modules, (2) Front & (2) Rear 27w Stationaries, 28 lbs.

See page 79 for Additional Mounting Adapters



